

RoofBlock™ Primer WB

a water-based, waterproofing primer formulated to provide excellent adhesion for RoofBlock™ HT, Product No.: 60404622

Product Description

RoofBlock Primer WB is for use with RoofBlock HT vapor barrier underlayment system.

BASIC USE

- **Prime as needed** all structural concrete, masonry, wood, fiber reinforced exterior sheathing or exterior gypsum board surfaces on which RoofBlock HT will be applied.
- Designed to be used in ambient temperatures and surface temperatures of 40°F (5°C) and rising.
- Used on both vertical and horizontal surfaces.

MATERIALS

RoofBlock Primer WB is a water-based, rubber-based, low-tack primer which is specifically formulated to provide excellent adhesion. It has a VOC content of 5 grams/liter.

Installation

APPLICATION

RoofBlock Primer WB may be applied with roller or brush.

Apply RoofBlock Primer WB to a clean, dry, dust free, and frost free surface at a coverage rate of approximately 350 to 400 square feet per gallon on concrete.

Exterior gypsum sheathing board products will vary in texture, performance and porosity. The coverage rate for RoofBlock Primer WB will vary due to substrate texture and porosity. Specific testing for coverage is recommended.

The primer should be spread sufficiently to avoid areas of excess material. Areas of excess material will lengthen the curing time on the application of the RoofBlock Primer WB.

LIMITATIONS

Limit the application of primer to what can be covered with RoofBlock HT in one working day. Any areas not covered with membrane during the day must be recoated. Be sure to cover all open containers when not applying primer.

Availability

VaproShield products are available throughout North America, Central and South America, and New Zealand.

PHYSICAL PROPERTIES	
PROPERTY	RESULT
Color	Orange
5 Gallon Pail	Product No.: 60404622
VOC Content	5 grams/liter
Application Temperature	40°F (5°C)

