

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900
Customer Service: (989) 496-6000
Product Disposal Information: (989) 496-6315
CHEMTREC: (800) 424-9300

MSDS No.: 04084682

Revision Date: 2011/09/14

Generic Description: Silicone Sealant
Physical Form: Paste
Color: White
Odor: Characteristic odor

NFPA Profile: Health 2 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTSAcute Effects

Eye: Direct contact may cause moderate irritation.
Skin: May cause mild irritation.
Inhalation: Overexposure by inhalation may cause drowsiness, dizziness, confusion or loss of coordination.
Oral: Swallowing large amounts may cause drowsiness.

Prolonged/Repeated Exposure Effects

Skin: Repeated skin contact may cause allergic skin reaction.
Inhalation: No known applicable information.
Oral: Overexposure by ingestion may injure the following organ(s): Blood.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
2224-33-1	3.0 - 7.0	Vinyltri (methylethylketoxime) silane
107-51-7	3.0 - 7.0	Octamethyltrisiloxane

The above components are hazardous as defined in 29 CFR 1910.1200.

4. FIRST AID MEASURES

Eye:	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 - 20 minutes while holding the eyelid(s) open. If contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin:	As quickly as possible remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately flush with lukewarm gently flowing water for 15 minutes. Completely decontaminate clothing, shoes and leather goods before reuse or discard. If irritation persists, obtain medical advice.
Inhalation:	Remove from the source of contamination or move to fresh air. If irritation persists, obtain medical advice.
Oral:	Never give anything by mouth if victim is rapidly losing consciousness or convulsing. DO NOT INDUCE VOMITING. Have victim drink 2 to 8 oz. (60 to 240 mL) of water. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Have victim rinse mouth with water again. Obtain medical attention.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES

Flash Point:	Not applicable.
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire Hazards:	None.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up:	Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.
-----------------------	--

Note: See Section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime (MEKO) within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally. Avoid skin contact.

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

CAS Number	Component Name	Exposure Limits
2224-33-1	Vinyltri (methylethylketoxime) silane	See ethyl methyl ketoxime comments.
107-51-7	Octamethyltrisiloxane	Dow Corning guide: TWA 200 ppm.

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

Ethyl methyl ketoxime is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within the following exposure guidelines: Vendor guide TWA: 3 ppm, STEL: 10 ppm; AIHA WEEL TWA: 10 ppm.

Engineering Controls

Local Ventilation: Recommended.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Personal Protective Equipment for Spills

Eyes: Use full face respirator.

Skin: Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

Precautionary Measures: Avoid eye contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally. Avoid skin contact. Use reasonable care.

Comments: Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime (MEKO) within exposure guidelines or use respiratory protection.

When heated to temperatures above 150°C (300°F) in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate eyes, nose, and throat. Safe handling conditions may be maintained by keeping vapor conditions within the OSHA permissible exposure limit for formaldehyde.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste

Color: White

Odor: Characteristic odor

Specific Gravity @ 25°C: 1.39

Viscosity: Not determined.

Freezing/Melting Point: Not determined.

Boiling Point: > 35C/95F

Vapor Pressure @ 25°C: Not determined.

Vapor Density: Not determined.

Solubility in Water: Not determined.

pH: Not determined.

Volatile Content: Not determined.

Flash Point: Not applicable.

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form as described in Section 8.

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANTHazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde. Silicon dioxide. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATIONComponent Toxicology Information

During use of the material, small amounts of methylethylketoxime (MEKO) will be released. Long-term or repeated exposure to high concentrations of oxime-silanes may cause narcotic type effects on the nervous system, harmful effects on the blood (anemia) and irritate nasal passages, but these effects are reversible and not considered serious. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed significant increases in liver tumor rates.

This material contains octamethyltrisiloxane (L3). Repeated exposure in rats to L3 resulted in what appears to be protoporphyrin accumulation in the liver at dose levels that exceed typical workplace or consumer exposures. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown. Industrial, commercial, or consumer intended uses of products containing L3 do not represent a risk to humans.

Special Hazard Information on ComponentsSensitizers

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
2224-33-1	3.0 - 7.0	Vinyltri (methylethylketoxime) silane	Possible skin sensitizer.

12. ECOLOGICAL INFORMATIONEnvironmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION

DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

Remarks: THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE SIZES WHERE THE HAZARDOUS SUBSTANCE DOES NOT MEET THE REPORTABLE QUANTITY.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical ListingsSection 302 Extremely Hazardous Substances (40 CFR 355):

None.

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

Section 304 CERCLA Hazardous Substances (40 CFR 302):

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
1330-20-7	0.2	Xylene

Section 311/312 Hazard Class (40 CFR 370):

Acute: Yes
Chronic: Yes
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
100-41-4	<0.1000	Ethylbenzene	Carcinogenic.
108-88-3	<0.0100	Toluene	Developmental toxin.

Massachusetts

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
68988-56-7	15.0 - 35.0	Trimethylated silica

DOW CORNING(R) 758 SILICONE WEATHER BARRIER SEALANT

70131-67-8	15.0 - 35.0	Dimethyl siloxane, hydroxy-terminated
2224-33-1	3.0 - 7.0	Vinyltri (methylethylketoxime) silane
107-51-7	3.0 - 7.0	Octamethyltrisiloxane

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
68988-56-7	15.0 - 35.0	Trimethylated silica
70131-67-8	15.0 - 35.0	Dimethyl siloxane, hydroxy-terminated
2224-33-1	3.0 - 7.0	Vinyltri (methylethylketoxime) silane
107-51-7	3.0 - 7.0	Octamethyltrisiloxane

16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark