AIR BARRIER SOLUTIONS



WHAT IS AN AIR BARRIER SOLUTION?

An air barrier system must be continuous. The system consists of



indoor air quality over the life of the building.

An air barrier system (red line) part of a continuous system. must be continuous Research has demonstrated that air leakage through the building envelope can transport exponentially more moisture through the building envelope than water vapor by diffusion. Controlling air flow can reduce problems such as corrosion, wall component deterioration and mold growth. Other benefits are improved energy efficiency and

A 2005 NIST¹ study showed that an effective air barrier can reduce a building's energy costs by as much as 40% and electrical costs by more than 25%.

VaproShield Vapor Permeable Air Barrier Solutions

WRAPSHIELD SA® SELF-ADHERED Water Resistive Vapor Permeable Air Barrier Membrane and accessories pass the rigorous ASTM E2357 test, the assembly recorded an air leakage difference of less than 0.01 cfm/ft², far exceeding the acceptable air leakage of .04 cfm/ft². Other mechanically attached VaproShield Membranes² have been tested to ASTM 2178 and competitively demonstrate impressive performance as a primary air barrier system component.

materials (individual compo-

nents), assemblies (such as

windows) and connections

be connected in a manner

that is capable of resisting

and remain durable. A product is not an air

positive and negative loads

barrier on its own, it must be

between them. Components of the air barrier system must



VaproShield LLC | 915 26th Ave. N.W. Suite C5 | Gig Harbor, WA 98335 | Toll Free: 1.866.731.7663 | www.VaproShield.com | © VaproShield 2/2013 VaproShield Canada | 101-1001 West Broadway Suite 545 | Vancouver, B.C. V6H 4E4, Canada | Toll Free: 1.866.871.8263 | www.VaproShield.ca

VAPROSHIELD AFFORDABLE **AIR BARRIER SOLUTIONS**



Save Energy

Air barrier technology reduces energy consumption.



Affordable

VaproShield Air Barrier Solutions are competitively priced and offer labor saving features.



All Climate Construction

Install VaproShield materials year round and in all climates; 0° to 120°F, (-17° to 49°C).



Compatible Systems

VaproShield materials can be installed on most substrates and building types.



Healthy Buildings

Zero VOC's, no primers, recyclable.

AIR BARRIER SOLUTIONS

VAPROSHIELD® Breathable Membrane Systems for Roofs & Walls

UNDERSTANDING AIR BARRIER TESTING

ASTM E2357 Air Leakage of Air Barrier Assemblies



<u>Standard</u>

Measures air permeance (leakage) of air barrier materials/accessories when combined into a wall assembly with pipe penetrations, brick ties, electrical boxes, foundation transitions, lap seams and flashings.

Bottom Line: ASTM E2357 is a more REALISTIC test method emulating installed materials on a building.

ASTM E2178 Air Permeance of Building Materials



<u>Standard</u>

• Only measures air permeance (leakage) of an air barrier material.



Contact VaproShield to learn more about Affordable Energy Saving Air Barriers. We provide technical assistance and have representatives throughout the US and Canada who offer knowledge and expertise about building envelope design and familiarity with local building codes and requirements.

1. National Institute of Standards and Technology (NIST), NISTIR 7238 Investigation of the Impact of Commercial Building Envelope Airtightness on HVAC Energy Use

2. WRAPSHIELD, REVEALSHIELD

VaproShield LLC | 915 26th Ave. N.W. Suite C5 | Gig Harbor, WA 98335 | Toll Free: 1.866.731.7663 | www.VaproShield.com | © VaproShield 2/2013 VaproShield Canada | 101-1001 West Broadway Suite 545 | Vancouver, B.C. V6H 4E4, Canada | Toll Free: 1.866.871.8263 | www.VaproShield.ca