

## WrapShield SA Self-Adhered applied WrapShield SA Self-Adhered applied WrapShield SA Self-Adhered applied

WrapShield SA Self-Adhered applied directly to Hunter XCI NB Vertical Nailable Polyiso Insulation

Gypsum sheathing (by others) in "as new" condition

Contact VaproShield for NFPA 285 compliance information

Cladding attached to vertical hat channels for rain screen design (by others)

## <u>Cladding screws should not</u> <u>penetrate field membrane</u>.

Hat channel screws penetrate into studs.

Hunter XCI NB Vertical Nailable Polyiso Insulation



PRODUCT DESCRIPTION

WrapShield SA is a self-adhered, water resistive vapor permeable air barrier sheet membrane

## DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR

REF: 172-A

DATE: 07.27.16

Always check www.VaproShield.com for the latest details and installation instructions

VaproShield LLC | 915 26th Ave. N.W. Suite C5 | Gig Harbor, WA 98335 | Toll Free: 1.866.731.7663 | www.VaproShield.com | © VaproShield VaproShield Canada | 101-1001 West Broadway Suite 545 | Vancouver, B.C. V6H 4E4, Canada | Toll Free: 1.866.871.8263 | www.VaproShield.ca