

Air Barriers At-a-Glance

A quick overview of top benefits

	WRAPSHIELD SA™ SELF-ADHERED	PANELSHIELD™ SA	REVEALSHIELD SA™ SELF-ADHERED	BLOCKSHIELD™ SA	RAINSCREEN SA™	CANSHIELD™ VP
Description	Spun-bond polypropylene	Proprietary polyacrylic coating on spun-bond polyester	Spun-bond polyester with permanent UV exposure	Non-asphaltic, air, water, and vapor barrier	Spun-bond polypropylene with factory-bonded rainscreen matrix	Multiple layers of spun-bond polypropylene
Vapor Permeable/Perms	50 perms	26 perms	63 perms	0.01	25 perms	25 perms
Vapor Impermeable				●		
Air Barrier	●	●	●	●	●	●
Exposure before permanent cladding	180 days	365 days	365 days	365 days	60 days	180 days
UV Stable for permanent exposure (between open joints)			●			
Below freezing application (20° and rising)	●	●	●	●	●	●
Substrate Compatibility	All except OSB	All	All except OSB	All	All	All
Zero VOCs	●	●	●	●	●	●
NFPA 285 Compliant Assemblies*	●	*	●	*		*
ABAA Evaluated	●		●			
Declare Label	●					
Warranty	20 year material warranty					

*Contact VaproShield Technical for additional NFPA 285 assembly information.