

SELF-ADHERED

For Low Slope/Flat Roofs

VaproBond or VaproLiqui-Flash at all post/column, and other penetrations.

VaproTape at all horizontal and vertical seams

HIELD SA

SlopeShield Plus installed with shingled laps (where sloped/applicable)

Walls with VaproShield membrane installed according to installation instructions

SHIELD SA

HIELD'SA

SlopeFlashing installed on eaves and gables of roof, extending down to shingle over wall membrane

SHIELD



DATE: 01/07/19

PRODUCT DESCRIPTION

SHIELD SA

SHIELD SA

SlopeShield Plus Self-Adhered is a highly vapor permeable roofing underlayment Air Barrier (AB) material

DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR

Ref: 259

Always check www.VaproShield.com for the latest details and installation instructions

VaproShield LLC | 915 26th Ave. N.W. Suite C5 | Gig Harbor, WA 98335 | Toll Free: 1.866.731.7663 | www.VaproShield.com | © VaproShield VaproShield Canada | 101-1001 West Broadway Suite 545 | Vancouver, B.C. V6H 4E4, Canada | Toll Free: 1.866.871.8263 | www.VaproShield.ca