


# Step 1: Nail Flange Window RO Flashing System:

RevealFlashing SA Self-Adhered scraps  
adhere to cover pre-punched metal stud holes

Sheathing in "as new"  
condition



## VAPROLIQUI-FLASH™

Step 1: Inspect rough opening,  
patch pre-punched holes with  
RevealFlashing SA

### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR

DATE: 11/12/23


REF: 324-1

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions

## Step 2: Nail Flange Window RO Flashing System:

RevealFlashing SA Self-Adhered scraps adhere to cover pre-punched metal stud holes

Sheathing in "as new" condition



RevealFlashing SA Self-Adhered properly shingled; applied directly to sheathing + folded 2.75" inside of R.O.

**Note:** Total of 11.75" of flashing should be used:

- 9" of flashing should be left on the face of the sheathing
- 6" of release film from the bottom of the flashing to be left attached for shingling over membrane.

### VAPROLIQUI-FLASH™

Step 2: Install RevealFlashing SA into sill with 2.75" folded into R.O. 9" left on face, with bottom 6" of release film to remain attached.

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.


DRAWN BY: AR

DATE: 11/12/23

REF: 324-2

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions

## Step 3: Nail Flange Window RO Flashing System:



RevealFlashing SA Self-Adhered properly shingled;  
applied directly to sheathing + folded 2.75" inside of R.O.

**Note:** Total of 11.75" of flashing should be used:

- 9" of flashing should be left on the face of the sheathing
- 6" of release film from the bottom of the flashing to be left attached for shingling over membrane.

### VAPROLIQUI-FLASH™

Step 3: Install jamb pieces with  
2.75" folded into R.O. 9" to be left  
on face.

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR

DATE: 11/12/23

REF: 324-3


Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions

## Step 4: Nail Flange Window RO Flashing System:

RevealFlashing SA Self-Adhered properly shingled;  
applied directly to sheathing + folded 2.75" inside of R.O.

**Note:** Total of 11.75" of flashing should be used:

- 9" of flashing should be left on the face of the sheathing
- 6" of release film from the bottom of the flashing to be left attached for shingling over membrane.



### VAPROLIQUI-FLASH™

Step 4: Install head piece with  
2.75" folded into R.O. 9" to be left  
on face.

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR


DATE: 11/12/23

REF: 324-4

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions

## Step 5: Nail Flange Window RO Flashing System:

VaproLiqui-Flash  
full-coverage inside  
rough opening + 1" on  
face



### VAPROLIQUI-FLASH™

Step 5: Apply VaproLiqui-Flash to  
inside of R.O. (full coverage) and  
1" on face

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied,  
vapor permeable, waterproof, air  
barrier flashing system component for  
window and door rough openings.  
VaproLiquiFlash is designed to work  
with RevealFlashing and VaproShield  
field membranes as a complete  
system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best  
practices for VaproShield materials, and does not  
represent a specific job site condition and therefore may  
not be applicable to certain projects. Detail sketch is  
designed for use as a reference and must be approved by  
the designer/ consultant of record for each project prior to  
installation by the subcontractor. Changes and approvals  
of VaproShield details are the sole responsibility of the  
designer/consultant of record. VaproShield is **not** the  
designer of record for building enclosure details and takes  
no responsibility for the accuracy or interpretation of  
actual project site conditions.

DRAWN BY: AR

DATE: 11/12/23


REF: 324-5

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions

## Step 6: Nail Flange Window RO Flashing System:

Nail Flange Window w/  
sealant joint + backer  
rod (by others)

Head flashing (by others  
over cured VaproLiqui-Flash)



### VAPROLIQUI-FLASH™

Step 6: Install nail flange window  
w/ perimeter sealant joint and  
backer rod (by others)

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR


DATE: 11/12/23

REF: 324-6

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions



## Step 7: Nail Flange Window RO Flashing System:



RevealShield SA Self-Adhered field membrane installed underneath 6" flap of RevealFlashing SA to create shingle effect

### VAPROLIQUI-FLASH™

Step 7: Install metal head flashing (by others) over cured VaproLiqui-Flash and install field membrane, shingled underneath window flashing

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.


DRAWN BY: AR

DATE: 11/12/23

REF: 324-7

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions

## Step 8: Nail Flange Window RO Flashing System:



### VAPROLIQUI-FLASH™

Step 8: Install field membrane vertically to sheathing, maintaining 3" minimum overlap with R.O. flashing

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR

DATE: 11/12/23


REF: 324-8

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions



## Step 9: Nail Flange Window RO Flashing System:

RevealShield SA Self-Adhered  
installed over head flashing and  
RevealFlashing SA



### VAPROLIQUI-FLASH™

Step 9: Install field membrane over metal head flashing, maintaining 3" minimum overlap to adjacent field membrane.

#### PRODUCT DESCRIPTION

VaproLiqui-Flash is a liquid applied, vapor permeable, waterproof, air barrier flashing system component for window and door rough openings. VaproLiquiFlash is designed to work with RevealFlashing and VaproShield field membranes as a complete system.

#### DISCLAIMER

Detail sketch is generic, representing suggested best practices for VaproShield materials, and does not represent a specific job site condition and therefore may not be applicable to certain projects. Detail sketch is designed for use as a reference and must be approved by the designer/ consultant of record for each project prior to installation by the subcontractor. Changes and approvals of VaproShield details are the sole responsibility of the designer/consultant of record. VaproShield is **not** the designer of record for building enclosure details and takes no responsibility for the accuracy or interpretation of actual project site conditions.

DRAWN BY: AR

DATE: 11/12/23

REF: 324-9

Always check [www.VaproShield.com](http://www.VaproShield.com) for the latest details and installation instructions