

NFPA 285 Compliant Wall Assembly

Exterior to Interior - Ref:1040

Terra Cotta, Xci Foil, Wood Stud

Terra Cotta, Xci Foil, Treated Wood Stud

View WRB placement variations p.2

WrapShield SA Self-Adhered is a self-adhered, water resistive (WRB) vapor permeable air barrier sheet membrane adhered directly to substrate.

RevealShield SA Self-Adhered is a black, UV stable, water resistive (WRB) vapor permeable self-adhered air barrier membrane for open joint rain screen cladding systems.

Per Chapter 26 of the International Building Code, the wall assembly shall be tested in accordance with and comply with the acceptance criteria of NFPA 285. The listed assemblies in this document have met that criteria according to Hunter Panels. Visit hunterpanels.com for verification.



Comprehensive details available at VaproShield.com.
Illustration for explanatory purposes only.

	mustration for explanatory pulposes only.
Wall Component	Materials
Base Wall System	FRTW (Fire-retardant-treated wood) studs: min norminal 2x4 dimension, spaced 24" o.c. (max) 5/8" type X Gypsum Wallboard Interior and Bracing as required by cude.
Approved Exterior Finish	Terra Cotta Cladding —Use any Terra Cotta Cladding System in which Terra Cotta is minimum 9/16". Any non-open joint installation technique or ventilated shiplap may be used.
Material Options	4" max thickness of Hunter Xci Foil
Floorline Firestopping	Mineral fiber based safing insulation in each cavity at the floor line. Safing thickness must match cavity depth. Or Solid FRTW blocking at floor line in accordance with building code requirements for Type III construction.
Stud Cavity	Any noncombustible insulation, Covestro BaySeal CC X or CC CP**, BASF Walltite**, NCFI InsulBlock SPF**, Icynene MD-C-200v3 (ProSeal) up to 5½" ** or None
Exterior Sheathing	1/2" (min) thick exterior gypsum sheathing OR $1/2$ " (min) FRTW structural panels in Type III construction. OR None*
Weather Resistive Membrane Applied to Base Wall	VaproShield WrapShield SA Self-Adhered, RevealShield SA Self-Adhered
Weather Resistive Membrane Applied	VaproShield WrapShield SA Self-Adhered, RevealShield SA Self-Adhered

The location and number of WRB's in the wall assembly are determined by the architect. See p.2 for additional illustrations showing VaproShield WRB/Air Barrier placement.

to Exterior Insulation



NFPA 285 Compliant Wall Assembly

Terra Cotta, Xci Foil, Wood Stud

VaproShield WRB/Air Barrier Placement Variations as per Hunter NFPA 285 Test Data





Comprehensive details available at VaproShield.com. Illustration for explanatory purposes only.